

專業自動洗地機

CT40



清潔劑由刷盤中心
順刷盤轉動平均噴灑
不浪費及污漬牆角



機械性浮動刷盤設計
適宜任何不平整地面清潔
使機器保持最佳清潔效率



V形水刮組設計
集水/吸水效率佳



直覺式簡易操作
符號及符合人體
工學設計

獨特科技設計

TCL微電腦充電器



補充式充電設計,有效管理電池使用效能
及延長電池組獨立使用年限



全自動操作功能程式設計:
出水系統/清洗刷/吸水馬達
同步啟動/關閉
吸水馬達延遲關閉設計



清洗刷裝卸/吸水膠片/水管
更新,皆不需使用任何工具

電池組



搭載AGM-EV等級深度放電免保養
電池,可節省保養費用及減低耗損成
本,電池材質採100%可回收物料

定量式清潔劑劑量調配器(選購)




清潔劑供應系統與供應水槽分離設計
可精確供應清潔劑量,節省成本
清潔劑供應桶不需工具即可裝/卸





清潔劑出水量及機器前進速度可依據工作需求微調



特殊防泡沫系統有效保護

- 當污水槽水位滿即自動停止吸水
- 清水槽無供應水時即自動停機



吸水刮組配備防刮牆角導輪,95%乳膠材質吸水膠片堅固耐用,特殊設計可四面更替使用



黃色保養區域指示及清洗刷毛耗損紅色指示,使保養更簡便



搭載高扭力齒輪箱馬達及高品質電路系統設計

Main technical characteristics

Motors

- **Brush rotation:** independent oil bath motor gear box
- **Suction:** 2 stages with stainless steel fans and shaft
- **Traction:** parallel axis differential with stainless steel bearings (BT version)

Plastics

- **Tanks:** great thickness high density polyethylene
- **Squeegee blades:** made in Latex usable on 4 sides
- **Hoses:** suction and discharge made in high resistance polyurethane
- **Wheels:** oil resistant

Other characteristics

- Nylon standard brushes with maximum consumption indicator
- Automatic brush click-on/off
- Electronic solution flow adjustment
- Positioned in height discharge hose (ø 40 mm)

Mechanics

- **Chassis:** double treatment with galvanizing + die-casting
- **Bearings:** shielded against humidity and water seepages
- **Bolts and nuts:** made in stainless steel where there are water contacts

Electric system

- **Carbon brushes:** easily changeable
- **Boards:** equipped with protective film against water and humidity
- **Solenoid valve:** with Viton membrane resistant against chemical agents
- **Sensors:** solution and recovery water level protected against accidental impacts
- **Display:** digital with hour counter and battery level



Control panel
Brushes, solution and vacuum inserted by one unique command or singularly upon necessity

機 型	清洗寬度 (mm)	吸水寬度 (mm)	清洗效率 (㎡/h)	刷盤數量	清水容量 (l)	污水容量 (l)	電力	前/後進速度 (Km/h)	淨重 (Kg)	體積 (LxWxH) (cm)
CT40 B55	550	850	1900	1	45	55	24V (2x12V)	3.5	67	1230x516x960
CT40 BT55	550	850	2475	1	45	55	24V (2x12V)	4.5/3	73	1230x516x960

* BT機型搭載驅動齒輪馬達

選購配件



權能國際股份有限公司

新北市三重區興德路86號4樓(遠見科技大樓)

電話: 02-29957337(代表) 傳真: 02-29957031

www.joynice.com.tw

inf@joynice.com.tw