

# 專業自動洗地機

## CT55



清潔劑由刷盤中心  
順刷盤轉動平均噴灑  
不浪費及污漬牆角



機械性浮動刷盤設計  
適宜任何不平整地面清潔  
使機器保持最佳清潔效率



V形水刮組設計  
集水/吸水效率佳



直覺式簡易操作  
符號及符合人體  
工學設計



全自動操作功能程式設計：  
出水系統/清洗刷/吸水馬達  
同步啟動/關閉  
吸水馬達延遲關閉設計



清洗刷裝卸/吸水膠片/水管  
更新,皆不需使用任何工具



### 獨特科技設計

TCL微電腦充電器



補充式充電設計,有效管理電池使用效能  
及延長電池組獨立使用年限

電池組



搭載AGM-EV等級深度放電免保養  
電池,可節省保養費用及減低耗損成  
本,電池材質採100%可回收物料


定量式清潔劑劑量調配器(選購)



清潔劑供應系統與供應水槽分離設計  
可精確供應清潔劑量,節省成本  
清潔劑供應桶不需工具即可裝/卸



清潔劑出水量及機器前進速度可依據工作需求微調



特殊防泡沫系統有效保護  
 ●當污水槽水位滿即自動停止吸水  
 ●清水槽無供應水時即自動停機



吸水刮組配備防刮牆角導輪,95%乳膠材質吸水膠片堅固耐用,特殊設計可四面更替使用



黃色保養區域指示及清洗刷毛耗損紅色指示,使保養更簡便



搭載高扭力齒輪箱馬達及高品質電路系統設計

## Main technical characteristics

### Motors

- **Brush rotation:** independent oil bath motor gear box
- **Suction:** 2 stages with stainless steel fans and shaft
- **Traction:** parallel axis differential with stainless steel bearings (BT version)

### Plastics

- **Tanks:** great thickness high density polyethylene
- **Squeegee blades:** made in Latex usable on 4 sides
- **Hoses:** suction and discharge made in high resistance polyurethane
- **Wheels:** oil resistant

### Other characteristics

- Nylon standard brushes with maximum consumption indicator
- Automatic brush click-on/off
- Electronic solution flow adjustment
- Positioned in height discharge hose (ø 40 mm)

### Mechanics

- **Chassis:** double treatment with galvanizing + die-casting
- **Bearings:** shielded against humidity and water seepages
- **Bolts and nuts:** made in stainless steel where there are water contacts

### Electric system

- **Carbon:** brushes easily changeable
- **Boards:** equipped with protective film against water and humidity
- **Solenoid valve:** with Viton membrane resistant against chemical agents
- **Sensors:** solution and recovery water level protected against accidental impacts
- **Display:** complete with hour counter and battery level



Control panel  
 Brushes, solution and vacuum inserted by one unique command or singularly upon necessity.

機 型	清洗寬度 (mm)	吸水寬度 (mm)	清洗效率 (㎡/h)	刷盤數量	清水容量 (l)	污水容量 (l)	電力	前/後進速度 (Km/h)	淨重 (Kg)	體積 (LxWxH) (cm)
CT55 B55	550	850	1925	1	55	60	24V (2x12V)	3.5	69	1190x640x1018
CT55 BT55	550	850	2475	1	55	60	24V (2x12V)	4.5	75	1190x640x1018
CT55 BT60	600	850	2700	2	55	60	24V (2x12V)	4.5	94	1190x640x1018

\* BT機型搭載驅動齒輪馬達

## 選購配件

