



***"Clean Floors with  
Clean-Green Energy"***

Get superior range without the inconvenience of having to add water or clean corrosive acid residue off your batteries with Fullriver maintenance-free batteries.

### **FULLRIVER BENEFITS:**

- **No watering and no corrosion damage – sealed AGM construction**
- **High capacity and long life – heavy duty thick plates**
- **High quality – built with superior materials and workmanship**
- **Safest battery – non-hazardous, non-gassing and non-spillable**

Fullriver batteries are available through our world-wide distribution network. For more information, please contact us toll-free at **(02)2995-7337** or visit our website at **[www.joynice.com.tw](http://www.joynice.com.tw)**

*Floor Care Equipment Batteries*

FULLRIVER DC SERIES: Specifications

| Model                                                        | Industry Ref. | Capacity (Minutes) |              | Capacity (AH)  |                 | Cranking (Amps) |             | Terminal Type<br>(See Below) | Dimensions - Inches (mm) |            |             | Weight<br>lbs. (kg) |
|--------------------------------------------------------------|---------------|--------------------|--------------|----------------|-----------------|-----------------|-------------|------------------------------|--------------------------|------------|-------------|---------------------|
|                                                              |               | @ 25<br>Amps       | @ 75<br>Amps | @ 5 Hr<br>Rate | @ 20 Hr<br>Rate | CA<br>@32°F     | CCA<br>@0°F |                              | Length                   | Width      | *Height     |                     |
| 6 Volt Deep Cycle - Sealed - Maintenance Free AGM Batteries  |               |                    |              |                |                 |                 |             |                              |                          |            |             |                     |
| DC224-6                                                      | GC2           | 441                | 113          | 179            | 224             | 1080            | 900         | M8-TP08                      | 10.24 (260)              | 7.09 (180) | 9.88 (251)  | 65.7 (29.8)         |
| DC245-6                                                      | DIN           | 457                | 120          | 198            | 245             | 1120            | 930         | AP                           | 9.61 (244)               | 7.48 (190) | 10.83 (275) | 71.2 (32.3)         |
| DC250-6                                                      | GC2           | 531                | 135          | 204            | 250             | 1160            | 960         | M8-TP08                      | 10.31 (262)              | 7.13 (181) | 10.71 (272) | 76.1 (34.5)         |
| DC335-6                                                      | 902/J305      | 751                | 184          | 274            | 335             | 1560            | 1300        | DT                           | 11.61 (295)              | 7.00 (178) | 14.41 (366) | 105.4 (47.8)        |
| DC400-6                                                      | 903/L16       | 885                | 229          | 340            | 415             | 1800            | 1500        | DT                           | 11.61 (295)              | 7.00 (178) | 16.69 (424) | 123.5 (56)          |
| 12 Volt Deep Cycle - Sealed - Maintenance Free AGM Batteries |               |                    |              |                |                 |                 |             |                              |                          |            |             |                     |
| DC70-12                                                      | 24            | 115                | 31           | 57.5           | 70              | 540             | 450         | M8-TP08                      | 10.24 (260)              | 6.65 (169) | 8.46 (215)  | 52.5 (23.8)         |
| DC85-12                                                      | 24            | 145                | 34           | 70             | 85              | 600             | 510         | M8-TP08                      | 10.24 (260)              | 6.65 (169) | 8.46 (215)  | 55.3 (25.1)         |
| DC105-12                                                     | 27            | 175                | 43           | 86             | 105             | 820             | 680         | M8-TP08                      | 12.09 (307)              | 6.65 (169) | 8.46 (215)  | 66.5 (30.2)         |
| DC115-12                                                     | 31            | 200                | 45           | 91             | 115             | 910             | 760         | M8-TP08                      | 12.91 (328)              | 6.77 (172) | 8.66 (220)  | 72.1 (32.7)         |
| DC140-12                                                     | DIN           | 260                | 62           | 115            | 140             | 950             | 795         | M8-TP08                      | 13.54 (344)              | 6.77 (172) | 11.14 (283) | 95.0 (43.1)         |
| DC145-12                                                     | NA            | 279                | 86           | 122            | 145             | 975             | 820         | M8                           | 13.43 (341)              | 6.81 (173) | 11.30 (287) | 97.7 (44.3)         |
| DC150-12                                                     | GC12          | 295                | 80           | 123            | 150             | 1050            | 900         | M8-TP08                      | 12.87 (327)              | 7.17 (182) | 10.75 (273) | 93.9 (42.6)         |
| DC215-12                                                     | 921/J185      | 420                | 110          | 172            | 215             | 1200            | 1000        | DT                           | 15.00 (381)              | 7.00 (178) | 14.61 (371) | 132.3 (60)          |

\* Heights will vary depending on what type of terminal used.

FULLRIVER DC SERIES: Terminal Configurations

To ensure quality and durability, Fullriver Battery utilizes the highest grade lead and brass when manufacturing our battery terminals.



M Terminal  
(M6 or M8)



TP Brass AP  
(TP07 or TP08)



AP & Stud Terminal  
(DT)



Automotive Post  
(AP)

Select batteries with the “M Terminal” are provided with the appropriate “Brass TP” screw-in AP posts. The M6 comes with the TP07 and the M8 comes with TP08. See the “Terminal Type” column above, or contact us for up-to-date product information.

Fullriver batteries are **NON-SPILLABLE** and **DOT, IATA, ICAO** and **IMDG** approved safe for transportation by land, air and sea.



For more information contact us at (02)2995-7337 or visit our website at [www.joynice.com.tw](http://www.joynice.com.tw)